# VK-3

# **WARRANTY REGISTRATION FORM**

Unit Serial Number:	
Customer Name:	
Address:	
radioss.	
Date of Purchase:	
Date of Furchase.	
D1	
Purchased From:	
B 1 W	
Dealer Name:	
Address:	

# **IMPORTANT NOTE:**

In order to receive the full five year product warranty, please mail this completed form together with a copy of your sales receipt to Balanced Audio Technology at the address below, within **thirty days** of purchase.

Failure to do so will result in the product being warrantied for **one year** from the date of manufacture.

# VK-3 Balanced Stereo Preamplifier

**Owner's Manual** 

#### Introduction

Thank you for your purchase of the Balanced Audio Technology VK-3 preamplifier. Please read this owner's manual to obtain the full benefit of the VK-3 in your system. It will provide you with the needed safety information and operating procedures for this exceptional unit.

#### **WARNINGS:**

To prevent the possibility of serious injury, electrical shock or fire:

**DO NOT** operate with the cover removed.

**DO NOT** expose to rain or moisture.

**DO NOT** defeat the ground power-plug.

**DO NOT** replace fuse with anything other than the same type and rating as supplied by the factory.

# **Package Contents**

Included in the box should be the following:

Description	Quantity	
VK-3 Preamplifier	1	
Power Cord	1	
Spare Fuse	1	
Torx Wrench (T-10)	1	
Spare Top Cover Screws	5	
User's Manual	1	
Optional Accessories	(as ordered)	

Save all the packaging material in a safe dry area for the unlikely event that you need to return the VK-3 to the factory for service.

# **Reseating Tubes**

Normally, reseating tubes upon delivery is not required. However, if any tubes have *noticeably* drifted out of position due to unusually high transportation stress, it will be advisable to reseat the tubes. Use the supplied Torx wrench to remove the top cover. Reseat the tubes in their sockets and reinstall the top cover.

**NOTE:** When using the Torx wrench, make sure it is fully inserted so that the screw head is not stripped.

## **Physical Placement**

It is recommended that you provide for at least 6" of free space around the unit for proper ventilation.

Mount the unit on a hard surface with proper ventilation underneath.

Do not stack the VK-3 preamplifier on top of other units, nor vice versa.

# Connecting the VK-3 to Your System

# **Balanced Components**

Use balanced XLR interconnects. All input and output connectors are clearly marked on the back panel.

**Note:** The VK-3 XLR connectors are wired as follows:

Pin 1: common/shield

Pin 2: positive Pin 3: negative

Use either the Main 1 or Main 2 Output for connection to your power amplifier. Both yield equivalent results.

# **Single-Ended Components**

Single-ended components have RCA connectors. The VK-3 preamplifier is designed to work with any mix of single-ended and balanced components connected to its inputs and outputs. All that is required to connect a single-ended component with RCA connectors to the VK-3's inputs or outputs is the optional balanced to single-ended adapters. These adapters are available from Balanced Audio Technology at a nominal charge.

Two types of adapters are available:

Input Adapters: RCA Female to XLR Male

Output Adapters: RCA Female to XLR Female.

#### Mixed Balanced and Single-Ended Systems

Any mix of single-ended and balanced components can be connected to the VK-3 by following the above instructions.

# **Description of Controls**

#### **Turning the VK-3 On:**

When you turn the unit On, the VK-3 will automatically go through a gentle POWER-ON sequence. During this time the filaments of the vacuum tubes are gradually brought to operating temperatures and the plate voltages are ramped up for maximum extention of tube life. At the end of this sequence the unit will automatically unmute, provided the Mute switch is in Play position. However, since the source volume may be unknown at this time, it is advisable to turn the volume control fully counterclockwise and place the mute switch in "Mute" position before powering the unit On.

#### **Turning the VK-3 Off:**

The unit can be turned Off at any time (even while playing) without first activating the Mute switch. It will automatically mute.

#### **Mute function:**

The VK-3 has two mute modes: manual and automatic. Putting the Mute switch in Mute position will always override the automatic function and disable the outputs.

When the unit is powered up it automatically self-mutes until the proper operating points of the circuitry are reached. It will then automatically go into Play mode, provided the Mute switch is in the Play position.

Changing the power switch position from On to Off even for short time, will make the unit reset its power sequencing circuit and mute its output. *It will then require about 45 seconds for the unit to become operational again.* 

#### **Fuse Protection:**

A blown fuse in the VK-3 is an indication of a serious problem. If a replacement fuse fails as well, no further attempts should be undertaken. Please contact the factory for professional service.

The proper fuse ratings are as follows:

For 100-120 VAC Units: 2A 250V Slow Blow

For 200-240 VAC Units: 1A 250V Slow Blow

Factory supplied fuses should be only replaced with the same type and rating parts.

### **Servicing**

The Balanced Audio Technology VK-3 should require no service other than changing tubes to maintain its high performance. The vacuum tubes used in the VK-3 are quality 6922s and 6V6's rated for approximately 5000 hours of use. Please direct any further service inquiries to the factory.

# Cleaning

To remove dust, occasionally wipe the front and top surfaces of your VK-3 with a damp soft cloth. If fingerprints appear, you may use a mild, non-alkaline soap solution. Do not use abrasive cleaners, as they may damage the fine finish of the unit.

# **Five Year Limited Warranty**

#### **Terms and Conditions**

#### 1. Limited Warranty

Upon receipt of the attached warranty registration form, Balanced Audio Technology warrants the purchased product to be free from manufacturing, materials, and workmanship defects for **five years** from date of original purchase, excepting vacuum tubes, subject to the following conditions. **Failure to return the enclosed registration form within 30 days from original purchase will result in a warranty period of one year from the date of manufacture.** 

#### 2. Vacuum Tubes

Vacuum tubes (including replacements under warranty) are warranted for one year from the date of the original VK-3 purchase.

# 3. Limited to Original Purchaser

This warranty is for the sole benefit of the original purchaser of the covered product, and may not be transferred to a subsequent purchaser of the product.

#### 4. Conditions and Limitations

This warranty is subject to certain conditions and limitations, as follows. This warranty is void and inapplicable if the product has not been used in accordance with the instructions found elsewhere in this manual, or if it has been misused or abused, damaged by accident or neglect, or in transport once in possession of the purchaser. The warranty is also void if the product has been repaired, modified, or tampered with by anyone other than Balanced Audio Technology or its specifically authorized agents.

#### 5. Remedy

If this product contains a materials, manufacturing, or workmanship defect that cannot be repaired at the dealership where the product was purchased, it must be packed in original packaging and returned to Balanced Audio Technology via insured freight, at the owners expense. If replacement packaging materials are required, they will be supplied by the factory at a nominal charge. **Returned products must be accompanied by a written description of the defect, and a return authorization number (available from the factory via phone or fax).** Upon receipt of defective product, Balanced Audio Technology agrees to repair the product without charge for parts (except vacuum tubes if the unit is more than one year old), or labor. The product will then be returned via prepaid, insured freight, with carrier at the sole determination of Balanced Audio Technology. This constitutes the purchasers sole remedy.

# 6. Design Changes

Balanced Audio Technology reserves the right to modify its products or change specifications at any time without obligation or liability to previous purchasers.

#### 7. Miscellaneous

Any implied warranties relating to the above product shall be limited to the duration of this warranty. This warranty does not extend to any incidental or consequential costs or damages to the purchaser. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.